

SCHEDULE 6

PROCEDURES FOR DEMAND RESOURCES AND ENERGY EFFICIENCY

A. Parties can partially or wholly offset the amounts payable for the Locational Reliability Charge with Demand Resources that are operated under the direction of the Office of the Interconnection. FRR Entities may reduce their capacity obligations with Demand Resources that are operated under the direction of the Office of the Interconnection and detailed in such entity's FRR Capacity Plan. Demand Resources qualifying under the criteria set forth below may be offered for sale or designated as Self-Supply in the Base Residual Auction, included in an FRR Capacity Plan, or offered for sale in any Incremental Auction, for any Delivery Year for which such resource qualifies. Qualified Demand Resources generally fall in one of three categories, i.e., Guaranteed Load Drop, Firm Service Level, or Legacy Direct Load Control (prior to June 1, 2016), as further specified in section G below and the PJM Manuals. Qualified Demand Resources may be provided by a Curtailment Service Provider, notwithstanding that such Curtailment Service Provider is not a Party to this Agreement. Such Curtailment Service Providers must satisfy the requirements hereof and the PJM Manuals.

Formatted: Indent: First line: 0"

1. A Party must formally notify, in accordance with the requirements of the PJM Manuals and section F hereof, as applicable, the Office of the Interconnection of the Demand Resource that it is placing under the direction of the Office of the Interconnection. A Party must further notify the Office of the Interconnection whether the resource is a Limited Demand Resource, an Extended Summer Demand Resource, a Base Capacity Demand Resource, a Summer-Period Demand Resource or an Annual Demand Resource.

Formatted: Indent: Left: 0.5", First line: 0"

2. A Demand Resource must achieve its full load reduction within the following time period:

Formatted: Indent: Left: 0.5", First line: 0"

(a) For the 2014/2015 Delivery Year, Curtailment Service Providers may elect a notification time period from the Office of the Interconnection of 30, 60 or 120 minutes prior to their Demand Resources being required to fully respond to a Load Management Event.

Formatted: Indent: Left: 0.5", First line: 0.1"

(b) For the 2015/2016 Delivery Year and subsequent Delivery Years, a Demand Resource must be able to fully respond to a Load Management Event within 30 minutes of notification from the Office of the Interconnection. This default 30 minute prior notification shall apply unless a Curtailment Service Provider obtains an exception from the Office of the Interconnection due to physical operational limitations that prevent the Demand Resource from reducing load within that timeframe. In such case, the Curtailment Service Provider shall submit a request for an exception to the 30 minute prior notification requirement to the Office of the Interconnection, at the time the Registration Form for that resource is submitted in accordance with Tariff, Attachment K-Appendix of this Tariff. The only alternative notification times that the Office of Interconnection will permit, upon approval of an exception request, are 60 minutes and 120 minutes prior to a Load Management Event. The Curtailment Service Provider shall indicate in writing, in the appropriate application, that it seeks an exception to permit a prior notification time

Formatted: Indent: Left: 0.5", First line: 0.1"

of 60 minutes or 120 minutes, and the reason(s) for the requested exception. A Curtailment Service Provider shall not submit a request for an exception to the default 30 minute notification period unless it has done its due diligence to confirm that the Demand Resource is physically incapable of responding within that timeframe based on one or more of the reasons set forth below and as may be further defined in the PJM Manuals and has obtained detailed data and documentation to support this determination.

In order to establish that a Demand Resource is reasonably expected to be physically unable to reduce load in that timeframe, the Curtailment Service Provider that registered the resource must demonstrate that:

~~2~~(i) The manufacturing processes for the Demand Resource require gradual reduction to avoid damaging major industrial equipment used in the manufacturing process, or damage to the product generated or feedstock used in the manufacturing process;

~~3~~(ii) Transfer of load to back-up generation requires time-intensive manual process taking more than 30 minutes;

~~3~~(iii) On-site safety concerns prevent location from implementing reduction plan in less than 30 minutes; or,

~~4~~(iv) The Demand Resource is comprised of mass market residential customers or Small Commercial Customers which collectively cannot be notified of a Load Management Event within a 30-minute timeframe due to unavoidable communications latency, in which case the requested notification time shall be no longer than 120 minutes.

The Office of the Interconnection may request data and documentation from the Curtailment Service Provider and such Curtailment Service Provider shall provide to the Office of the Interconnection within three (3) Business Days of a request therefor, a copy of all of the data and documentation supporting the exception request. Failure to provide a timely response to such request shall cause the exception to terminate the following Operating Day.

At its sole option and discretion, the Office of the Interconnection may review the data and documentation provided by the Curtailment Service Provider to determine if the Demand Resource has met one or more of the criteria above. The Office of the Interconnection will notify the Curtailment Service Provider in writing of its determination by no later than ten (10) Business Days after receipt of the data and documentation.

The Curtailment Service Provider shall provide written notification to the Office of the Interconnection of a material change to the facts that supported its exception request within three (3) Business Days of becoming aware of such material change in facts, and, if the Office of Interconnection determines that the physical limitation criteria above are no longer being met, the Demand Resource shall be subject to the default notification period of 30 minutes immediately upon such determination.

Formatted: Indent: Left: 0", First line: 0.5"

Formatted: Indent: Left: 1", First line: 0"

Formatted: Indent: Left: 1", First line: 0"

Formatted: Indent: Left: 1", First line: 0"

Formatted: Indent: Left: 1", First line: 0"

Formatted: Indent: Left: 0", First line: 0.5"

Formatted: Indent: Left: 0", First line: 0.5"

Formatted: Indent: First line: 0.5"

3. The initiation of load reduction, upon the request of the Office of the Interconnection, must be within the authority of the dispatchers of the Party. No additional approvals should be required.

Formatted: Indent: Left: 0.5", First line: 0"

4. The initiation of load reduction upon the request of the Office of the Interconnection is considered a pre-emergency or emergency action and must be implementable prior to a voltage reduction.

Formatted: Indent: Left: 0.5", First line: 0"

5. A Curtailment Service Provider intending to offer for sale or designate for self-supply, a Demand Resource in any RPM Auction, or intending to include a Demand Resource in any FRR Capacity Plan must demonstrate, to PJM's satisfaction, that such resource shall have the capability to provide a reduction in demand, or otherwise control load, on or before the start of the Delivery Year for which such resource is committed. As part of such demonstration, each such Curtailment Service Provider shall submit a Demand Resource Sell Offer Plan in accordance with the standards and procedures set forth in ~~RAA, section A-1 of~~ Schedule 6, ~~section A-1; RAA,~~ Schedule 8.1 (as to FRR Capacity Plans); and the PJM Manuals, no later than 15 Business Days prior to, as applicable, the RPM Auction in which such resource is to be offered, or the deadline for submission of the FRR Capacity Plan in which such resource is to be included. PJM may verify the Curtailment Service Provider's adherence to the Demand Resource Sell Offer Plan at any time. A Curtailment Service Provider with a PJM-approved Demand Resource Sell Offer Plan will be permitted to offer up to the approved Demand Resource quantity into the subject RPM Auction or include such resource in its FRR Capacity Plan.

Formatted: Indent: Left: 0.5", First line: 0"

Formatted: Highlight

6. Selection of a Demand Resource in an RPM Auction results in commitment of capacity to the PJM Region. Demand Resources that are so committed must be registered to participate in the Full Program Option or as a Capacity Only resource of the Emergency Load Response and Pre-Emergency Load Response Program and thus available for dispatch during PJM-declared pre-emergency events and emergency events.

Formatted: Indent: Left: 0.5", First line: 0"

A-1. A Demand Resource Sell Offer Plan shall consist of a completed template document in the form posted on the PJM website, requiring the information set forth below and in the PJM Manuals, and a Demand Resource Officer Certification Form signed by an officer of the Demand Resource Provider that is duly authorized to provide such a certification. The Demand Resource Sell Offer Plan must provide information that supports the Demand Resource Provider's intended Demand Resource Sell Offers and demonstrates that the Demand Resources are being offered with the intention that the MW quantity that clears the auction is reasonably expected to be physically delivered through Demand Resource registrations for the relevant Delivery Year. The Demand Resource Sell Offer Plan shall include all Existing Demand Resources and all Planned Demand Resources that the Demand Resource Provider intends to offer into an RPM Auction or include in an FRR Capacity Plan.

Formatted: Indent: Left: 0.5", First line: 0"

1. Demand Resource Sell Offer Plan Template. The Demand Resource Sell Offer Plan template, in the form provided on the PJM website, shall require the

Formatted: Indent: Left: 1", First line: 0"

Demand Resource Provider to provide the following information and such other information as specified in the PJM Manuals:

(a) Summary Information. The completed template shall include the Demand Resource Provider's company name, contact information, and the Nominated DR Value in ICAP MWs by Zone/sub-Zone that the Demand Resource Provider intends to offer, stated separately for Existing Demand Resources and Planned Demand Resources. The total Nominated DR Value in MWs for each Zone/sub-Zone shall be the sum of the Nominated DR Value of Existing Demand Resources and the Nominated DR Value of Planned Demand Resources, and shall be the maximum MW amount the Provider intends to offer in the RPM Auction for the indicated Zone/sub-Zone, provided that nothing herein shall preclude the Demand Resource Provider from offering in the auction a lesser amount than the total Nominated DR Value shown in its Demand Resource Sell Offer Plan.

Formatted: Indent: Left: 1.5", First line: 0"

(b) Existing Demand Resources. The Demand Resource Provider shall identify all Existing Demand Resources by identifying end-use customer sites that are currently registered with PJM (even if not registered by such Demand Resource Provider) and that the Demand Resource Provider reasonably expects to have under a contract to reduce load based on PJM dispatch instructions by the start of the auction Delivery Year.

Formatted: Indent: Left: 1.5", First line: 0"

(c) Planned Demand Resources. The Demand Resource Provider shall provide the details of, and key assumptions underlying, the Planned Demand Resource quantities (i.e., all Demand Resource quantities in excess of Existing Demand Resource quantities) contained in the Demand Resource Sell Offer Plan, including:

Formatted: Indent: Left: 1.5", First line: 0"

(i) key program attributes and assumptions used to develop the Planned Demand Resource quantities, including, but not limited to, discussion of:

Formatted: Indent: Left: 1.75"

- method(s) of achieving load reduction at customer site(s);
- equipment to be controlled or installed at customer site(s), if any;
- plan and ability to acquire customers;
- types of customer targeted;
- support of market potential and market share for the target customer base, with adjustments for Existing Demand Resource customers within this market and the potential for other Demand Resource Providers targeting the same customers;
- assumptions regarding regulatory approval of program(s), if applicable; and

Formatted: Indent: First line: 0"

Formatted: Indent: Left: 2", Hanging: 0.5"

Formatted: Indent: First line: 0"

Formatted: Indent: Left: 2", Hanging: 0.5"

- Prior to June 1, 2016: if applicable, Legacy Direct Load Control (LDLC) program details such as: a description of the cycling control strategy, any assumptions regarding switch operability rate, and a list (and copy) of all load research studies used to develop the estimated nominated ICAP value per customer (i.e., the per-participant impact).

(ii) Zone/sub-Zone information by end-use customer segment for all Nominated DR Values for which an end-use customer site is not identified, to include the number in each segment of end-use customers expected to be registered for the subject Delivery Year, the average Peak Load Contribution per end-use customer for such segment, and the average Nominated DR Value per customer for such segment. End-use customer segments may include residential, commercial, small industrial, medium industrial, and large industrial, as identified and defined in the PJM Manuals, provided that nothing herein or in the Manuals shall preclude the Provider from identifying more specific customer segments within the commercial and industrial categories, if known.

Formatted: Indent: Left: 1.75"

(iii) Information by end-use customer site to the extent required by subsection A-1(1)(c)(iv) or, if not required by such subsection, to the extent known at the time of the submittal of the Demand Resource Sell Offer Plan, to include: customer EDC account number (if known), customer name, customer premise address, Zone/sub-Zone in which the customer is located, end-use customer segment, current Peak Load Contribution value (or an estimate if actual value not known) and an estimate of expected Peak Load Contribution for the subject Delivery Year, and an estimated Nominated DR Value.

(iv) End-use customer site-specific information shall be required for any Zones or sub-Zones identified by PJM pursuant to this subsection for the portion, if any, of a Demand Resource Provider's intended offer in such Zones or sub-Zones that exceeds a Sell Offer threshold determined pursuant to this subsection, as any such excess quantity under such conditions should reflect Planned Demand Resources from end-use customer sites that the Provider has a high degree of certainty it will physically deliver for the subject Delivery Year. In accordance with the procedures in subsection A-1(3) below, PJM shall identify, as requiring site-specific information, all Zones and sub-Zones that comprise any LDA group (from a list of LDA groups stated in the PJM Manuals) in which [the quantity of cleared Demand Resources from the most recent Base Residual Auction] plus [the quantity of Demand Resources included in FRR Capacity Plans for the Delivery Year addressed by the most recent Base Residual Auction] in any Zone or sub-Zone of such LDA group exceeds the greater of:

- the maximum Demand Resources quantity registered with PJM for such Zone for any Delivery Year from the current (at time of plan submission) Delivery Year and the two preceding Delivery Years; and
- the potential Demand Resource quantity for such Zone estimated by PJM based on an independent published assessment of demand response potential that is reasonably applicable to such Zone, as identified in the PJM Manuals.

Formatted: Indent: Left: 2", Hanging: 0.5"

Formatted: Indent: Left: 2", Hanging: 0.5"

For each such Zone and sub-Zone, the Sell Offer threshold for each Demand Resource Provider shall be the higher of:

Formatted: Indent: Left: 1.75"

- the Demand Resource Provider's maximum Demand Resource quantity registered with PJM for such Zone/sub-Zone over the current Delivery Year (at the time of plan submission) and two preceding Delivery Years;
- the Demand Resource Provider's maximum for any single Delivery Year of [such provider's cleared Demand Resource quantity] plus [such provider's quantity of Demand Resources included in FRR Capacity Plans] from the three forward Delivery Years addressed by the three most recent Base Residual Auctions for such Zone/sub-Zone; and
- 10 MW.

Formatted: Indent: Left: 2", Hanging: 0.5"

Formatted: Indent: Left: 2", Hanging: 0.5"

Formatted: Indent: First line: 0"

(d) Schedule. The Demand Resource Provider shall provide an approximate timeline for procuring end-use customer sites as needed to physically deliver the total Nominated DR Value (for both Existing Demand Resources and Planned Demand Resources) by Zone/sub-Zone in the Demand Resource Sell Offer Plan. The Demand Resource Provider must specify the cumulative number of customers and the cumulative Nominated DR Value associated with each end-use customer segment within each Zone/sub-Zone that the Demand Resource Provider expects (at the time of plan submission) to have under contract as of June 1 each year between the time of the auction and the subject Delivery Year.

Formatted: Indent: Left: 1", First line: 0"

2.—Demand Resource Officer Certification Form. Each Demand Resource Sell Offer Plan must include a Demand Resource Officer Certification, signed by an officer of the Demand Resource Provider that is duly authorized to provide such a certification, in the form shown in the PJM Manuals, which form shall include the following certifications:

Formatted: Indent: Left: 0.5", First line: 0"

(a) that the signing officer has reviewed the Demand Resource Sell Offer Plan and the information supplied to PJM in support of the Plan is true and correct as of the date of the certification; and

Formatted: Indent: Left: 1", First line: 0"

(b) that the Demand Resource Provider is submitting the Plan with the reasonable expectation, based upon its analyses as of the date of the certification, to physically deliver all megawatts that clear the RPM Auction through Demand Resource registrations by the specified Delivery Year.

Formatted: Indent: Left: 1", First line: 0"

As set forth in the form provided in the PJM ~~m~~Manuals, the certification shall specify that it does not in any way abridge, expand, or otherwise modify the current provisions of the PJM Tariff, Operating Agreement and/or RAA, or the Demand Resource Provider's rights and obligations thereunder, including the Demand Resource Provider's ability to adjust capacity obligations through participation in PJM incremental auctions and bilateral transactions.

Formatted: Indent: First line: 0.5"

3. Procedures. No later than December 1 prior to the Base Residual Auction for a Delivery Year, PJM shall post to the PJM website a list of Zones and sub-Zones, if any, for which end-use customer site-specific information shall be required under the conditions specified in subsection A-1(1)(c)(iv) above for all RPM Auctions conducted for such Delivery Year. Once so identified, a Zone or sub-Zone shall remain on the list for future Delivery Years until the threshold determined under subsection A-1(1)(c)(iv) above is not exceeded for three consecutive Delivery Years. No later than 15 Business Days prior to the RPM Auction in which a Demand Resource Provider intends to offer a Demand Resource, the Demand Resource Provider shall submit to PJM a completed Demand Resource Sell Offer Plan template and a Demand Resource Officer Certification Form signed by a duly authorized officer of the Provider. PJM will review all submitted DR Sell Offer Plans. No later than 10 Business Days prior to the subject RPM Auction, PJM shall notify any Demand Resource Providers that have identified the same end-use customer site(s) in their respective DR Sell Offer Plans for the same Delivery Year. In such event, the MWs associated with such site(s) will not be approved for inclusion in a Sell Offer in an RPM Auction by any of the Demand Resource Providers, unless a Demand Resource Provider provides a letter of support from the end-use customer indicating that it is likely to execute a contract with that Demand Resource Provider for the relevant Delivery Year, or provides other comparable evidence of likely commitment. Such letter of support or other supporting evidence must be provided to PJM no later than 7 Business Days prior to the subject RPM Auction. If an end-use customer provides letters of support for the same site for the same Delivery Year to multiple Demand Resource Providers, the MWs associated with such end-use customer site shall not be approved as a Demand Resource for any of the Demand Resource Providers. No later than 5 Business Days prior to the subject RPM Auction, PJM will notify each Demand Resource Provider of the approved Demand Resource quantity, by Zone/sub-Zone, that such Demand Resource Provider is permitted to offer into such RPM Auction.

Formatted: Indent: Left: 1", First line: 0"

B. The Unforced Capacity value of a Demand Resource will be determined as:

for the Delivery Years through May 31, 2018, or for FRR Capacity Plans for Delivery Years through May 31, 2019, the product of the Nominated Value of the Demand Resource, times the DR Factor, times the Forecast Pool Requirement, and for the 2018/2019 Delivery Year and subsequent Delivery Years, or for FRR Capacity Plans the 2019/2020 Delivery Year and subsequent Delivery Years, the product of the Nominated Value of the Demand Resource times the Forecast Pool Requirement. Nominated Values shall be determined and reviewed in accordance with sections I and J, respectively, and the PJM Manuals. The DR Factor is a factor established by the PJM Board with the advice of the Members Committee to reflect the increase in the peak load carrying capability in the PJM Region due to Demand Resources. Peak load carrying capability is defined to be the peak load that the PJM Region is able to serve at the loss of load expectation defined in the Reliability Principles and Standards. The DR Factor is the increase in the peak load carrying capability in the PJM Region due to Demand Resources, divided by the total Nominated Value of Demand Resources in the PJM Region. The DR Factor will be determined using an analytical program that uses a probabilistic approach to determine reliability. The determination of the DR Factor will consider the reliability of Demand Resources, the number of interruptions, and the total amount of load reduction.

C. Demand Resources offered and cleared in a Base Residual or Incremental Auction shall receive the corresponding Capacity Resource Clearing Price as determined in such auction, in accordance with ~~Tariff, Attachment DD of the PJM Tariff~~. For Delivery Years beginning with the Delivery Year that commences on June 1, 2013, any Demand Resources located in a Zone with multiple LDAs shall receive the Capacity Resource Clearing Price applicable to the location of such resource within such Zone, as identified in such resource's offer. Further, the Curtailment Service Provider shall register its resource in the same location within the Zone as specified in its cleared sell offer, and shall be subject to deficiency charges under ~~Tariff, Attachment DD of this Tariff~~ to the extent it fails to provide the resource in such location consistent with its cleared offer. For either of the Delivery Year commencing on June 1, 2010 or commencing on June 1, 2012, if the location of a Demand Resource is not specified by a Seller in the Sell Offer on an individual LDA basis in a Zone with multiple LDAs, then Demand Resources cleared by such Seller will be paid a DR Weighted Zonal Resource Clearing Price, determined as follows: (i) for a Zone that includes non-overlapping LDAs, calculated as the weighted average of the Resource Clearing Prices for such LDAs, weighted by the cleared Demand Resources registered by such Seller in each such LDA; or (ii) for a Zone that contains a smaller LDA within a larger LDA, calculated treating the smaller LDA and the remaining portion of the larger LDA as if they were separate LDAs, and weight-averaging in the same manner as (i) above.

D. The Party, Electric Distributor, or Curtailment Service Provider that establishes a contractual relationship (by contract or tariff rate) with a customer for load reductions is entitled to receive the compensation specified in section C for a committed Demand Resource, notwithstanding that such provider is not the customer's energy supplier.

E. Any Party hereto shall demonstrate that its Demand Resources performed during periods when load management procedures were invoked by the Office of the Interconnection. The Office of the Interconnection shall adopt and maintain rules and procedures for verifying the performance of such resources, as set forth in section K hereof and the PJM Manuals. In addition, committed Demand Resources that do not comply with the directions of the Office of the Interconnection to reduce load during an emergency shall be subject to the penalty charge set forth in Tariff, Attachment DD ~~to the PJM Tariff~~.

F. Parties may elect to place Demand Resources associated with Behind The Meter Generation under the direction of the Office of the Interconnection for a Delivery Year by submitting a Sell Offer for such resource (as Self Supply, or with an offer price) in the Base Residual Auction for such Delivery Year. This election shall remain in effect for the entirety of such Delivery Year. In the event such an election is made, such Behind The Meter Generation will not be netted from load for the purposes of calculating the Daily Unforced Capacity Obligations under this Agreement.

G. PJM measures Demand Resources in the following ways:

Prior to June 1, 2016: Legacy Direct Load Control (LDLC) – Load management that is initiated directly by the Curtailment Service Provider’s market operations center or its agent, employing a communication signal to cycle equipment (typically water heaters or central air conditioners). DLC programs are qualified based on load research and customer subscription data. Curtailment Service Providers may rely on the results of load research studies identified in the PJM Manuals to set the per-participant load reduction for LDLC programs. Each Curtailment Service Provider relying on DLC load management must periodically update its LDLC switch operability rates, in accordance with the PJM Manuals.

Firm Service Level (FSL) – Load management achieved by an end-use customer reducing its load to a pre-determined level (the Firm Service Level), upon notification from the Curtailment Service Provider’s market operations center or its agent.

Guaranteed Load Drop (GLD) – Load management achieved by an end-use customer reducing its load by a pre-determined amount (the Guaranteed Load Drop), upon notification from the Curtailment Service Provider’s market operations center or its agent. Typically, the load reduction is achieved through running customer-owned backup generators, or by shutting down process equipment.

H. Each Curtailment Service Provider must satisfy (or contract with another LSE, Curtailment Service Provider, or electric distribution company to provide) the following requirements:

- A point of contact with appropriate backup to ensure single call notification from PJM and timely execution of the notification process;

Formatted: Indent: First line: 0"

- Supplemental status reports, detailing Demand Resources available, as requested by PJM;
- Entry of customer-specific Demand Resource credit information, for planning and verification purposes, into the designated PJM electronic system.
- Customer-specific compliance and verification information for each PJM-initiated Demand Resource event or Provider initiated test event, as well as aggregated Provider load drop data for Provider-initiated events, in accordance with established reporting guidelines.
- Load drop estimates for all Demand Resource events and test events, prepared in accordance with the PJM Manuals.

Formatted: Indent: First line: 0"

Formatted: Indent: First line: 0"

Formatted: Indent: First line: 0"

Formatted: Indent: First line: 0"

I. The Nominated Value of each Demand Resource shall be determined consistent with the process for determination of the capacity obligation for the customer.

The Nominated Value for a Firm Service Level customer will be based on the peak load contribution for the customer, as typically determined by the 5CP methodology utilized by the electric distribution company to determine ICAP obligation values. The Nominated Value for Annual Demand Resources with a Capacity Performance commitment shall equal the lessor of i) total peak load contribution for the customers on the registration minus the nominated summer Firm Service Level multiplied by the loss factor and ii) total Winter Peak Load for customers on the registration multiplied by Zonal Winter Weather Adjustment Factor minus winter Firm Service level and then the result is multiplied by the loss factor. The Nominated Value for Limited Demand Resources, Extended Summer Demand Resources, Base Capacity Demand Resources, Summer Period Demand Resources, and Annual Demand Resources without a Capacity Performance Commitment shall be total peak load contribution for the customers on the registration minus the nominated summer Firm Service Level multiplied by the loss factor.

The Nominated Value for a Guaranteed Load Drop customer for Annual Demand Resources with a Capacity Performance commitment will be the lessor of the summer and winter guaranteed load drop amount, adjusted for system losses, as established by the customer's contract with the Curtailment Service Provider. The Nominated Value for a Guaranteed Load Drop customer for Limited Demand Resources, Extended Summer Demand Resources, Base Capacity Demand Resources, Summer Period Demand Resources, and Annual Demand Resources without a Capacity Performance Commitment will be the summer guaranteed load drop amount, adjusted for system losses, as established by the customer's contract with the Curtailment Service Provider. The maximum value nominated for any Demand Resource shall not exceed the customer's Peak Load Contribution.

Prior to June 1, 2016, the Nominated Value for a Legacy Direct Load Control program will be based on load research and customer subscription. The maximum value of the

program is equal to the approved per-participant load reduction multiplied by the number of active participants, adjusted for system losses. The per-participant impact is to be estimated at long-term average local weather conditions at the time of the summer peak.

Customer-specific Demand Resource information (EDC account number, peak load contribution, Winter Peak Load, notification period, etc.) will be entered into the designated PJM electronic system to establish nominated values. Additional data may be required, as defined in sections J and K and the PJM Manuals.

- J. Nominated Values shall be reviewed based on documentation of customer-specific data and Demand Resource information, to verify the amount of load management available and to set a maximum allowable Nominated Value. Data is provided by both the zone EDC and the Curtailment Service Provider on templates supplied by PJM, and must include the EDC meter number or other unique customer identifier, Peak Load Contribution (5CP), Winter Peak Load, contract firm service level or guaranteed load drop values, applicable loss factor, zone/area location of the load drop, number of active participants, etc. Such data must be uploaded and approved prior to the first day of the Delivery Year for such resource as a Demand Resource. Curtailment Service Providers must provide this information concurrently to host EDCs.

For Firm Service Level and Guaranteed Load Drop customers, the 5CP values, for the zone and affected customers, will be adjusted to reflect an “unrestricted” peak for a zone, based on information provided by the Curtailment Service Provider. Load drop levels shall be estimated in accordance with guidelines in the PJM Manuals.

Prior to June 1, 2016, for Legacy Direct Load Control programs, the Curtailment Service Provider must provide information detailing the number of active participants in each program. Other information on approved LDLC programs will be provided by PJM.

- K. Compliance is the process utilized to review Provider performance during PJM-initiated Demand Resource events and Curtailment Service Provider initiated tests. Compliance will be established for each Provider on an event specific basis for the Curtailment Service Provider’s Demand Resources dispatched by the Office of the Interconnection during such event. PJM will establish and communicate reasonable deadlines for the timely submittal of event data to expedite compliance reviews. Compliance reviews will be completed as soon after the event as possible, with the expectation that reviews of a single event will be completed within two months of the end of the month in which the event took place. Curtailment Service Providers are responsible for the submittal of compliance information to PJM for each PJM-initiated event and Curtailment Service Provider initiated test during the compliance period.

Compliance is measured for Market Participant Bonus Performance, as applicable, and Non-Performance Charges. Non-Performance Charges are assessed for the defined obligation period of each Demand Resource as defined in [RAA](#), Article 1, subject to the following requirements:

Prior to June 1, 2016, compliance for Legacy Direct Load Control programs will consider only the transmission of the control signal. Curtailment Service Providers are required to report the time period (during the Demand Resource event) that the control signal was actually sent.

Compliance is checked on an individual customer basis for Firm Service Level, by comparing actual load during the event to the firm service level. Current load for a statistical sample of end-use customers may be used for compliance for residential non-interval metered registrations in accordance with the PJM Manuals and subject to PJM approval. Curtailment Service Providers must submit actual customer load levels (for the event period) for the compliance report. Compliance for FSL will be based on:

Summer (June through October and the following May of a Delivery Year)- End use customer's current Delivery Year peak load contribution ("PLC") minus the metered load ("Load") multiplied by the loss factor ("LF"). The calculation is represented by:

$$(PLC) - (Load * LF)$$

Winter (November through April of a Delivery Year)- End use customer's Winter Peak Load ("WPL") multiplied by Zonal Winter Weather Adjustment Factor ("ZWWAF") multiplied by LF, minus the metered load ("Load") multiplied by the LF. The calculation is represented by:

$$(WPL * ZWWAF * LF) - (Load * LF)$$

Compliance is checked on an individual customer basis for Guaranteed Load Drop. Current load for a statistical sample of end-use customers may be used for compliance for residential non-interval metered registrations in accordance with the PJM Manuals and subject to PJM approval. Guaranteed Load Drop compliance will be based on:

- (i) the lesser of (a) comparison load used to best represent what the load would have been if PJM did not declare a Load Management Event or the CSP did not initiate a test as outlined in the PJM Manuals, minus the Load and then multiplied by the LF, or (b) For a summer event, the PLC minus the Load multiplied by the LF. A summer load reduction will only be recognized for capacity compliance if the Load multiplied by the LF is less than the PLC. For a non-summer event, the WPL multiplied the ZWWAF multiplied by LF, minus the Load multiplied by the LF. A non-summer load reduction will only be recognized for capacity compliance if the Load multiplied by the LF is less than the WPL multiplied by the ZWWAF multiplied by LF.
- (ii) Curtailment Service Providers must submit actual loads and comparison loads for all hours during the day of the Load Management Event or the Load Management performance test, and for all hours during any other days as required by the Office of the Interconnection to calculate the load reduction. Comparison loads must be

developed from the guidelines in the PJM Manuals, and note which method was employed.

- (iii) Methodologies for establishing comparison load for Guaranteed Load Drop end-use customers are described in greater detail in Manual M-19, PJM Manual for Load Forecasting and Analysis, at Attachment A: Load Drop Estimate Guidelines.

Compliance is averaged over the Load Management Event for non-interval metered LDLC programs, prior to June 1, 2016. Compliance is averaged over the Load Management Event for Demand Resource without a Capacity Performance commitment or on an hourly basis for Demand Resources with a Capacity Performance commitment, for each FSL and GLD customer dispatched by the Office of the Interconnection for at least 30 minutes of the clock hour (i.e., “partial dispatch compliance hour”). The registered capacity commitment for the partial dispatch compliance hour will be prorated based on the number of minutes dispatched during the clock hour and as defined in the Manuals. Curtailment Service Provider may submit 1 minute load data for use in capacity compliance calculations for partial dispatch compliance hours subject to PJM approval and in accordance with the PJM Manuals where: (a) metering meets all Tariff and Manual requirements, (b) 1 minute load data shall be submitted to PJM for all locations on the registration, and (c) 1 minute load data measures energy consumption over the minute.

For all Delivery Years:

Demand Resources may not reduce their load below zero (i.e., export energy into the system). No compliance credit will be given for an incremental load drop below zero. Compliance will be totaled over all FSL and GLD customers and LDLC programs (prior to June 1, 2016) to determine a net compliance position for the event for each Provider by Zone, for all Demand Resources committed by such Provider and dispatched by the Office of the Interconnection in the zone. Deficiencies shall be as further determined in accordance with ~~section 11 of Tariff, Schedule DD, section 11 to the PJM Tariff.~~

L. Energy Efficiency Resources

1. An Energy Efficiency Resource is a project, including installation of more efficient devices or equipment or implementation of more efficient processes or systems, exceeding then-current building codes, appliance standards, or other relevant standards, designed to achieve a continuous (during peak summer and winter periods as described herein) reduction in electric energy consumption at the End-Use Customer’s retail site that is not reflected in the peak load forecast prepared for the Delivery Year for which the Energy Efficiency Resource is proposed, and that is fully implemented at all times during such Delivery Year, without any requirement of notice, dispatch, or operator intervention.
2. An Energy Efficiency Resource may be offered as a Capacity Resource in the Base Residual or Incremental Auctions for any Delivery Year beginning on or after June 1, 2011. No later than 30 days prior to the auction in which the

resource is to be offered, the Capacity Market Seller shall submit to the Office of the Interconnection a notice of intent to offer the resource into such auction and a measurement and verification plan. The notice of intent shall include all pertinent project design data, including but not limited to the peak-load contribution of affected customers, a full description of the equipment, device, system or process intended to achieve the load reduction, the load reduction pattern, the project location, the project development timeline, and any other relevant data. Such notice also shall state the seller's proposed Nominated Energy Efficiency Value.

- For Delivery Years through May 31, 2018 for all Energy Efficiency Resources not committed as a Capacity Performance Resource, the seller's proposed Nominated Energy Efficiency Value shall be the expected average load reduction between the hour ending 15:00 EPT and the hour ending 18:00 EPT during all days from June 1 through August 31, inclusive, of such Delivery Year that is not a weekend or federal holiday;
- For the 2018/2019 and 2019/2020 Delivery Years, the seller's proposed Nominated Energy Efficiency Value for any Base Capacity Energy Efficiency Resource shall be the expected average load reduction between the hour ending 15:00 EPT and the hour ending 18:00 EPT during all days from June 1 through August 31, inclusive, of such Delivery Year that is not a weekend or federal holiday; and
- For the 2018/2019 Delivery Year and subsequent Delivery Years and for any Annual Energy Efficiency Resource committed as a Capacity Performance Resource for the 2016/2017 and 2017/2018 Delivery Years, the seller's proposed Nominated Energy Efficiency Value for any Annual Energy Efficiency Resources, shall be the expected average load reduction, for all days from June 1 through August 31, inclusive, of such Delivery Year that is not a weekend or federal holiday, between the hour ending 15:00 EPT and the hour ending 18:00 EPT. In addition, the expected average load reduction for all days from January 1 through February 28, inclusive, of such Delivery Year that is not a weekend or federal holiday, between the hour ending 8:00 EPT and the hour ending 9:00 EPT and between the hour ending 19:00 EPT and the hour ending 20:00 EPT shall not be less than the Nominated Energy Efficiency Value; and
- For the 2020/2021 Delivery Year and subsequent Delivery Years, the seller's proposed Nominated Energy Efficiency Value for any Summer-Period Energy Efficiency Resource shall be the expected average load reduction between the hour ending 15:00 EPT and the hour ending 18:00 EPT during all days from June 1 through August 31, inclusive, of such Delivery Year that is not a weekend or federal holiday.

The measurement and verification plan shall describe the methods and procedures, consistent with the PJM Manuals, for determining the amount of

the load reduction and confirming that such reduction is achieved. The Office of the Interconnection shall determine, upon review of such notice, the Nominated Energy Efficiency Value that may be offered in the Reliability Pricing Model Auction.

3. ~~An Energy Efficiency Resource may be offered with a price offer or as Self-Supply. If an Energy Efficiency Resource clears the auction, it shall receive the applicable Capacity Resource Clearing Price, subject to section 5 below. A Capacity Market Seller offering an Energy Efficiency Resource must comply with all applicable credit requirements as set forth in Tariff, Attachment Q to the PJM Tariff. For Delivery Years through May 31, 2018, or for FRR Capacity Plans for Delivery Years through May 31, 2019, the Unforced Capacity value of an Energy Efficiency Resource offered into an RPM Auction shall be the Nominated Energy Efficiency value times the DR Factor and the Forecast Pool Requirement. For the 2018/2019 Delivery Year and subsequent Delivery Years, or for FRR Capacity Plans for the 2019/2020 Delivery Year and subsequent Delivery Years, the Unforced Capacity value of an Energy Efficiency Resource offered into an RPM Auction shall be the Nominated Energy Efficiency Value times the Forecast Pool Requirement.~~
4. An Energy Efficiency Resource that clears an auction for a Delivery Year may be offered in auctions for up to three additional consecutive Delivery Years, but shall not be assured of clearing in any such auction; provided, however, an Energy Efficiency Resource may not be offered for any Delivery Year in which any part of the peak season is beyond the expected life of the equipment, device, system, or process providing the expected load reduction; and provided further that a Capacity Market Seller that offers and clears an Energy Efficiency Resource in a BRA may elect a New Entry Price Adjustment on the same terms as set forth in Tariff, Attachment DD, section 5.14(c) ~~of this Attachment DD~~.
5. For every Energy Efficiency Resource clearing an RPM Auction for a Delivery Year, the Capacity Market Seller shall submit to the Office of the Interconnection, by no later than 30 days prior to each Auction an updated project status and measurement and verification plan subject to the criteria set forth in the PJM Manuals.
6. For every Energy Efficiency Resource clearing an RPM Auction for a Delivery Year, the Capacity Market Seller shall submit to the Office of the Interconnection, by no later than the start of such Delivery Year, an updated project status and detailed measurement and verification data meeting the standards for precision and accuracy set forth in the PJM Manuals. The final value of the Energy Efficiency Resource during such Delivery Year shall be as determined by the Office of the Interconnection based on the submitted data.
7. The Office of the Interconnection may audit, at the Capacity Market Seller's expense, any Energy Efficiency Resource committed to the PJM Region. The

audit may be conducted any time including the Performance Hours of the Delivery Year.

8. For Incremental Auctions conducted for the 2019/2020 and 2020/2021 Delivery Years, and for RPM Auctions for the 2021/2022 Delivery Year and subsequent Delivery Years, if a Relevant Electric Retail Regulatory Authority receives FERC authorization to qualify or prohibit Energy Efficiency Resource participation in a specific area(s) of the PJM Region, the following process applies:

(a) The Office of the Interconnection will publicly post a reference to the FERC authorization of a Relevant Electric Retail Regulatory Authority order, ordinance or resolution that qualifies or prohibits Energy Efficiency Resource participation, the applicable electric distribution company(ies), and the applicable auction(s) and/or Delivery Year(s).

(b) A Capacity Market Seller that intends to offer or certify Energy Efficiency Resources must identify and itemize all resources that are located in the jurisdiction of a Relevant Electric Retail Regulatory Authority authorized by FERC to qualify or prohibit Energy Efficiency Resource participation within the Zone or LDA, as required, and those outside of the area but within the Zone or LDA, as required.

(c) A Capacity Market Seller that intends to offer or certify Energy Efficiency Resources must identify and itemize all Energy Efficiency Resources to be offered as part of its Energy Efficiency measurement and verification plan and certified post-installation measurement and verification report. The Office of Interconnection will provide a list of Capacity Market Sellers that are:

- (i) offering Energy Efficiency Resources in an RPM Auction within two (2) Business Days after the deadline for submitting an energy efficiency measurement and verification plan for such RPM Auction to the relevant electric distribution company for the specific area(s) to review for compliance with the Relevant Electric Retail Regulatory Authority.
- (ii) certifying Energy Efficiency Resources with a Delivery Year post-installation measurement and verification report, within two (2) Business Days of receipt of such Delivery Year post-installation measurement and verification report, to the relevant electric distribution company for the specific area(s) to review for compliance with the Relevant Electric Retail Regulatory Authority.

(d) The relevant electric distribution company for the specific area(s) shall review for compliance with rules from a Relevant Electric Retail Regulatory Authority authorized by FERC to qualify or prohibit Energy Efficiency Resource participation and provide a response to the Office of the Interconnection within five (5) Business Days after receiving the list of Capacity Market Sellers offering Energy Efficiency Resources. The Office of the Interconnection will not allow a Capacity Market Seller to offer or certify Energy Efficiency Resources if an electric distribution company denies such Capacity Market Seller to deliver Energy Efficiency Resources in compliance with rules of a Relevant Electric Retail Regulatory Authority authorized by FERC to qualify or prohibit Energy Efficiency Resource participation.

- (9) For Incremental Auctions that will be conducted for the 2019/2020 and 2020/2021 Delivery Years, and for RPM Auctions for the 2021/2022 Delivery Year and subsequent Delivery Years, a Capacity Market Seller of Energy Efficiency Resources that cannot satisfy its RPM obligations in any Delivery Year due to the prohibition of participation by a Relevant Electric Retail Regulatory Authority authorized by FERC to prohibit participation of such resources may be relieved of its Capacity Resource Deficiency Charge by notifying the Office of the Interconnection by no later than seven (7) calendar days prior to the posting of the planning parameters for the Third Incremental Auction of that Delivery Year. After providing such notice, the affected Capacity Market Seller may elect to be relieved of its RPM commitment, and shall not be required to obtain replacement capacity for the resource, and no penalty shall be assessed by the Office of the Interconnection for the Capacity Market Seller's deficiency in satisfying its RPM obligation for the resource for such Delivery Year. In such case, however, the Capacity Market Seller shall not be entitled to, nor be paid, any RPM revenues for such resource for that Delivery Year. The Office of the Interconnection will apply corresponding adjustments to the quantity of Buy Bids or Sell Offers in the Incremental Auctions for such Delivery Years in accordance with Tariff, Attachment DD, sections 5.12(b)(ii) and 5.12(b)(iii).